Digital Conferencing Systems

Don't miss a single sound.

Listen®

DCS 6000 30-Person Digital Conferencing System w/Voice Activation

Part Number: LS-75

The LS-75 is a portable conference system for 29 delegates and one (1) chairman. This system provides excellent sound quality and can operate either in a utomatic mixing (voice activation) mode or with delegate control. It is ideal for corporate training centers, rental companies and break-out or committee rooms that require voice activation. The LS-75 system is fully functional without any additional parts, can be set up in a matter of minutes and does not require an operator.

Includes:

(1) CU 6005
(29) DM 6010 P
(1) CM 6070
(1) EC 6000-10
(29) EC 6000-02
(1) FL 6000-3A

- Excellent sound quality.

- Cost-effective structured Cat-5e cabling.

- Automatic mixing mode with configurable threshold and release time.

- Remote microphone sensitivity control.

- Elegant, unobtrusive, black units.

DCS 6000 30-Person Touch Screen Digital Conferencing System w/Voting & PC

Part Number: LS-76

The LS-76 is a portable conference system with voting capabilities for 29 delegates and one (1) chairman. This system provides excellent sound quality and is configured to operate with delegate and PC control. It is ideal for city and county councils, committee rooms and rental applications with audience response. Each DC 6990 P microphone unit has a 3.5 in. (9 cm) touch-screen that can be configured per meeting for different voting facilities depending on the need. It also offers two (2) headphone jacks for assistive listening.

Includes:

(1) CU 6005
(30) DC 6990 P
(30) GM 6424
(1) EC 6000-10
(29) EC 6000-02
(1) FL 6000-4A
(1) SW 6000
(1) SW 6008
(1) SW 6060

- Excellent sound quality.

- Cost-effective structured Cat-5e cabling.

- 3.5 in touch-screen option.

- Headphone jacks for assistive listening or language interpretation.

- Up to 8 open microphones.

- Built-in automatic gain control.

- Yes/No/Abstain & multiple choice voting.

- Optional automatic mixing mode with configurable threshold and release time.

- Advanced PC meeting managements applications.

- SQL delegate database that integrates in other win app's.

- Web streaming application.

- Elegant, unobtrusive, black units.

Digital Conferencing Systems

DCS 6000 100-Person Shared Mic Digital Conferencing System w/2 Languages & PC Control

Part Number: LS-77

The LS-77 is a portable conference system with language interpretation for 28 delegates and two (2) chairmen. This system provides excellent sound quality and is configured to operate with delegate and PC control. It is ideal for meetings and rental applications that require language interpretation. The two (2) delegates per conference unit will share one (1) microphone and microphone button, but each have their own channel selector and volume control for personal language and volume preference.

- Excellent sound quality.
- Cost-effective structured Cat-5e cabling.
- Built-in simultaneous interpretation.
- Dual delegate units.
- Remote microphone sensitivity control.
- Up to 8 open microphones.
- Built-in automatic gain control.
- Elegant, unobtrusive, black units.

Includes:

(1) CU 6011	(2) LA-165
(48) DM 6070 P	(1) SW 6000
(2) CM 6070 P	(1) SW 6232
(2) IS 6132 P	(1) SW 6008
(2) GM 6424	
(3) EC 6000-10	
(1) EC 6000-05	
(48) EC 6000-02	

DCS 6000 30-Person Mount Digital Conferencing System w/Voting & PC Control

Part Number: LS-78

The LS-76 is a portable conference system with voting capabilities for 29 delegates and one (1) chairman. This system provides excellent sound quality and is configured to operate with delegate and PC control. It is ideal for city and county councils, committee rooms and rental applications with audience response. Each DC 6990 P microphone unit has a 3.5 in. (9 cm) touch-screen that can be configured per meeting for different voting facilities depending on the need. It also offers two (2) headphone jacks for assistive listening.

- Excellent sound quality.
- Cost-effective structured Cat-5e cabling.
- Built-in voting features.
- Custom flush-mount configurations.
- Remote microphone sensitivity control.
- Up to 8 open microphones.
- Built-in automatic gain control.
- Elegant, unobtrusive, black units.

Includes:

(1) CU 6005
(30) DC 6990 P
(30) GM 6424
(1) EC 6000-10
(29) EC 6000-02
(1) FL 6000-4A
(1) SW 6000
(1) SW 6008
(1) SW 6060